



# INSTALLATION TYPES



### WARNINGS:

- This frame is **ONLY** to be used on a flat non-sloped ceiling.
- Heater must face straight down.
- Frame and Heater cannot be installed on a pitched angle.
- Junction box must be installed outside of drywall pocket.

### NOTES:

- Heater suspends (Gravity) by resting on adjustable tabs in flush mount fixture.
- Mounting holes on Surface Flange to be determined and drilled by Contractor/Installer.
- Supplied with Hi-Temp Fixture Whip and Hi-Temp Ceramic Wire Nuts.
- **Note: Please contact factory for longer length whips available for purchase.**
- Coil excess flex into heater cavity.
- **Use Licensed Electrician ONLY**

<b>INFRATECH</b> www.infratech-usa.com		15700 S. Figueroa St. Gardena, California 90248 Phone: (310) 354-1250 Fax: (310) 523-3674
ITEM #: 18-2305	MATERIAL: 304 S.S. #4 FINISH	
DESCRIPTION: W-61 FLUSH MOUNT PLASTER FRAME (FOR USE WITH 6 1/4" HEATERS)		
NOTES: SUPPLIED w/ ELECTRICAL FIXTURE WHIP		
DATE: Dec.16, 2019	SCALE: N/A	DRAWN BY: MD